Material Safety Data Sheet



ALIGAL™ 15

1. Product and company identification

Product name : ALIGAL™ 15

Material uses : Special atmospheres for food.

Supplier/Manufacturer : Air Liquide Canada Inc.

1250, René-Lévesque West, Suite 1700

Montreal, QC H3B 5E6

www.airliquide.ca 1-800-817-7697

Prepared by : IHS

<u>In case of emergency</u> : (514) 878-1667

2. Hazards identification

Physical state : Gas.
Color : Colorless.
Odor : Odorless.

Emergency overview

Signal word : CAUTION!

Hazard statements : HIGH PRESSURE GAS. GAS REDUCES OXYGEN AVAILABLE FOR BREATHING.

CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON

ANIMAL DATA.

Precautions : Contains gas under pressure. In a fire or if heated, a pressure increase will occur and

the container may burst or explode. At very high concentrations, can displace the normal air and cause suffocation from lack of oxygen. Do not puncture or incinerate container. Do not enter storage areas and confined spaces unless adequately ventilated. Avoid breathing gas. Use only with adequate ventilation. Keep container

tightly closed and sealed until ready for use.

Routes of entry : Dermal contact. Eye contact. Inhalation.

Potential acute health effects

Inhalation : At very high concentrations, can displace the normal air and cause suffocation from lack

of oxygen. Exposure to decomposition products may cause a health hazard. Serious

effects may be delayed following exposure.

Ingestion: As this product is a gas, refer to the inhalation section.

Skin: Contact with rapidly expanding gas may cause burns or frostbite.Eyes: Contact with rapidly expanding gas may cause burns or frostbite.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.

Carcinogenicity
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

2. Hazards identification

Target organs

: Contains material which may cause damage to the following organs: lungs, cardiovascular system, upper respiratory tract, central nervous system (CNS).

Over-exposure signs/symptoms

Inhalation: No specific data.Ingestion: No specific data.Skin: No specific data.Eyes: No specific data.

Medical conditions aggravated by overexposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

3. Composition/information on ingredients

Name	CAS number	%
nitrogen	7727-37-9	55-85
Carbon dioxide	124-38-9	15-45

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

: As this product is a gas, refer to the inhalation section.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Antidote information

Product/ingredient name	Antidote information
No antidote information known	

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Flammability of the product

: Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

nitrogen oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8). If leak is in user's equipment, be certain to purge piping with an inert gas prior to attempting repairs. Never fix a leak while the system is under pressure. If leak is on container or container valve, contact the closest Air Liquide Canada location.

Environmental precautions

Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

Large spill

: Immediately contact emergency personnel. Stop leak if without risk.

: Immediately contact emergency personnel. Stop leak if without risk. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Valve protection caps must remain in place unless cylinder is secured with valve outlet piped to usage point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow to the cylinder. Do not tamper with (valve) safety device. Close valve after each use and when empty.

7. Handling and storage

Storage

: Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 52°C/125°F. Cylinders must be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in - first out" inventory system to prevent full cylinders being stored for excessive periods of time. Store in accordance with local regulations. Store in a segregated and approved area. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Protect from sunlight. Keep container tightly closed and sealed until ready for use.

8. Exposure controls/personal protection

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)			Ceiling				
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Carbon dioxide		5000 5000 5000 5000 5000	9000 9000 - 9000 9000	- - -	30000 15000 30000	54000 54000 - 54000 54000	- - -	- - - -	- - - -	-	[2]

[2]Oxygen Depletion [Asphyxiant]

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. If operating conditions cause high gas concentrations to be produced or any recommended or statutory exposure limit is exceeded, use an air-fed respirator or self-contained breathing apparatus. The gas can cause asphyxiation without warning by replacing the oxygen in the air. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Exposure controls/personal protection 8.

Eyes : Safety eyewear complying with an approved standard should be used when a risk

> assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before

handling this product.

Environmental exposure

controls

Skin

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Physical and chemical properties 9.

Physical state : Gas.

Not available. Flash point : Not available. **Auto-ignition temperature** Flammable limits : Not available. Color : Colorless. Odor : Odorless. рH : Not available.

Boiling/condensation point : -195.79°C (-320.4°F)

Melting/freezing point : -209.99°C (-346°F) This is based on data for the following ingredient: Nitrogen

Critical temperature : -146.9°C (-232.4°F) **Density** : 1.5356 to 1.7141 g/l Not available. Vapor pressure

: Not available. Vapor density : Not available. **Odor threshold** Not available. **Evaporation rate** : Not available. **Viscosity**

Solubility : Partially soluble in the following materials: cold water.

LogKow : Not available.

Stability and reactivity 10.

Chemical stability : The product is stable. : No specific data. Conditions to avoid

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

: No specific data.

Possibility of hazardous

Incompatible materials

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity

Not available.

Chronic toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitizer

Not available.

Carcinogenicity

Classification

Not available.

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Not available.

Persistence/degradability

Not available.

Partition coefficient: n-

octanol/water

: Not available.

: Not available.

Bioconcentration factor

Mobility : Not available.

Toxicity of the products of

: Not available.

biodegradation

Other adverse effects: No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Empty pressure vessels should be returned to the supplier. Waste packaging should be recycled.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Disposal considerations 13.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Transport information 14.

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	UN1956	COMPRESSED GAS, N.O.S. (nitrogen, Carbon dioxide)	2.2	-		Explosive Limit and Limited Quantity Index 0.12 Passenger Carrying Road or Rail Index 75
IMDG Class	UN1956	COMPRESSED GAS, N.O.S. (nitrogen, Carbon dioxide)	2.2	-		Emergency schedules (EmS) F-C, S-V
IATA-DGR Class	UN1956	Compressed gas, n.o. s. (Carbon dioxide, nitrogen)	2.2	-	2	Passenger and Cargo Aircraft Quantity limitation: 75 kg Packaging instructions: 200 Cargo Aircraft Only Quantity limitation: 150 kg Packaging instructions: 200 Limited Quantities - Passenger Aircraft Quantity limitation: Forbidden Packaging instructions: Forbidden

PG*: Packing group

Regulatory information

United States inventory

(TSCA 8b)

: All components are listed or exempted.

WHMIS (Canada)

: Class A: Compressed gas.

Canadian lists

Canadian NPRI : None of the components are listed.

CEPA Toxic substances : The following components are listed: Carbon dioxide

Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists : Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined.

Korea inventory: All components are listed or exempted. Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted. Taiwan inventory (CSNN): All components are listed or exempted.

ALIGAL™ 15

15. Regulatory information

Chemical Weapons

: Not listed

Convention List Schedule I Chemicals

Chemical Weapons

: Not listed

Convention List Schedule

II Chemicals

Chemical Weapons

: Not listed

Convention List Schedule

III Chemicals

16. Other information

Label requirements

: HIGH PRESSURE GAS. GAS REDUCES OXYGEN AVAILABLE FOR BREATHING. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Date of issue : 6/1/2014.

Date of previous issue : 6/15/2011.

Version : 6

Indicates information that has changed from previously issued version.

Notice to reader

THE INFORMATION, RECOMMENDATIONS AND DATA CONTAINED IN THIS DOCUMENT ARE INTENDED TO BE USED BY PROPERLY TRAINED AND QUALIFIED PERSONNEL ONLY AND AT THEIR SOLE RISKS AND DISCRETION. THE INFORMATION, RECOMMENDATIONS AND DATA HEREIN CONTAINED ARE DERIVED FROMSOURCES WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, AIR LIQUIDE CANADA INC. MAKES NO REPRESENTATION AND GIVES NO WARRANTY OF ANY KIND WHATSOEVER WITH RESPECT TO THEIR ACCURACY OR COMPLETENESS AND ASSUMES NO LIABILITY FOR DAMAGES OR LOSS ARISING DIRECTLY OR INDIRECTLY FROM THEIR USE, WHETHER PROPER OR IMPROPER.

Notes ALIGAL™: Trademark of L'Air Liquide S.A.