



Printing date 09/04/2014 Version 6 Reviewed on 09/04/2014

1 Identification of substance

· Product details

· Trade name: Stainshield Universal

Article number: 146-03-0001
 Creation date: 10/10/2008

· Manufacturer/Supplier:

Linde Canada Limited Linde

5860 Chedworth Way

Mississauga, Ontario L5R 0A2

Telephone (905) 501-1700

575 Mountain Avenue

Murray Hill, NJ 07974

Telephone (908) 464-8100

24-HOUR EMERGENCY TELEPHONE NUMBER: 24-HOUR EMERGENCY TELEPHONE NUMBER

: (905) 501-0802 CHEMTREC (800) 424-9300 OR

Linde National Operations Center (800) 232-4726

Pse ensure that this MSDS is received by the appropriate person.

· Information department: Customer Service Centre: 1-866-385-5349

2 Composition/Data on components

- · Chemical characterization
- · Dangerous components: Void

· Chemical components		
7440-59-7	Helium	23 - <60%
7440-37-1	Argon	23 - <60%
124-38-9	Carbon Dioxide	0.1- < 5%

3 Hazards identification

- · Hazard description:
- · WHMIS-symbols:

A - Compressed gas



· HMIS-ratings (scale 0 - 4)



· NFPA ratings (scale 0 - 4)



· Information pertaining to particular dangers for man and environment: Not applicable.

(Contd. on page 2)

Printing date 09/04/2014 Version 6 Reviewed on 09/04/2014

Trade name: Stainshield Universal

(Contd. of page 1)

· Classification system:

The classification is in line with internationally approved calculation standards. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

· GHS label elements



2.5/C - Contains gas under pressure; may explode if heated.

Protect from sunlight. Store in a well-ventilated place.

4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for at least 15 minutes under running water. Then consult a doctor.
- · After swallowing: Not applicable

5 Fire fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

· Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventillation.

Stop leak - ONLY if possible to do so without risk.

- · Measures for environmental protection: Prevent seepage into sewage system, workpits and/or cellars.
- **Measures for cleaning/collecting:** Ensure adequate ventillation.
- · Additional information: No dangerous substances are released.

7 Handling and storage

- · Handling:
- · Information for safe handling:

Handle with care. Avoid jolting, friction, and impact.

Use only in well ventilated areas.

Store container in a secured area. Limit access to authorized personnel only. Report any incidents involving thefts, misuse, or inventory shortages to law enforcement and the supplier. Security shall be provided in accordance with all local, state (provincial) and federal regulations.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Do not expose cylinder to temperatures higher than 50°C (122 °F)

(Contd. on page 3)

Printing date 09/04/2014 Version 6 Reviewed on 09/04/2014

Trade name: Stainshield Universal

(Contd. of page 2)

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125°F (52°C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time.

· Information about storage in one common storage facility:

Sources of ignition should be removed from storage area.

· Further information about storage conditions:

Store in accordance with local fire code and/or building code or any pertaining regulations.

8 Exposure controls and personal protection

· Additional information about design of technical systems:

Adequate local ventillation.

Safety showers and eyewash stations should be nearby.

· Components with limit values that require monitoring at the workplace:

7440-59-7 Helium (23 - <60%)

EL Simple asphyxiant

7440-37-1 Argon (23 - <60%)

EL Simple asphyxiant

124-38-9 Carbon Dioxide (0.1- < 5%)

EL Short-term value: 15000 ppm Long-term value: 5000 ppm

EV Short-term value: 54.000 mg/m³, 30.000 ppm Long-term value: 9.000 mg/m³, 5.000 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Protective clothing and PPE should be kept free of oil and grease, generally in clean condition PPE should be inspected and maintained regularly to retain effectiveness.

· Breathing equipment:

Use atmosphere-supplying respirators (e.g. supplied-air: demand, pressure-demand, or continuous-flow or self-contained breathing apparatus: demand or pressure-demand or combination supplied-air with auxiliary self-contained air supply atmosphere-supplying respirator) in case of insufficient ventilation.

· Protection of hands:



Protective gloves.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Eye protection: Safety glasses

9 Physical and chemical properties

· General Information		
Form:	Gaseous.	
Color:	Not Applicable	
Odor:	Odorless	

(Contd. on page 4)

Printing date 09/04/2014 Version 6 Reviewed on 09/04/2014

Trade name: Stainshield Universal

(Contd. of page 3)

· Change in condition

Boiling point/Boiling range: -185°C

· Flash point: Not applicable.

• **Danger of explosion:** Product does not present an explosion hazard.

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Materials to be avoided:
- · Dangerous reactions No dangerous reactions known.
- · Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: LC50 None available
- · Primary irritant effect:
- · on the skin: No irritating effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

12 Ecological information

- · Additional ecological information:
- · General notes: Generally not hazardous for water

13 Disposal considerations

- · Product:
- **Recommendation:** Unused product should be returned to vendor.
- · Uncleaned packagings:
- · Recommendation:

Cylinder and unused product should be returned to vendor. Disposable cylinder must be disposed of in accordance with local regulations.

 \cdot Recommended cleansing agent: None applicable.

14 Transport information

· TDG and DOT regulations:



· Hazard class:

· Identification number: UN1956

(Contd. on page 5)

Printing date 09/04/2014 Version 6 Reviewed on 09/04/2014

Trade name: Stainshield Universal

(Contd. of page 4)

· Proper shipping name (technical name): COMPRESSED GAS, N.O.S.

· Label 2.2

· Maritime transport IMDG:



IMDG Class: 2
UN Number: 1956
Label 2.2
Marine pollutant: No

· Proper shipping name: COMPRESSED GAS, N.O.S.

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 2 · UN/ID Number: 1956 · Label 2.2

· **Propper shipping name:** COMPRESSED GAS, N.O.S.

· UN "Model Regulation": UN1956, COMPRESSED GAS, N.O.S., 2.2

15 Regulations

·Sara

 \cdot Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

(Contd. on page 6)

Printing date 09/04/2014 Version 6 Reviewed on 09/04/2014

Trade name: Stainshield Universal

(Contd. of page 5)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Canadian substance listings:

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

124-38-9 Carbon Dioxide

· Product related hazard informations:

Observe the general safety regulations when handling chemicals.

The product is not subject to identification regulations according to directives on hazardous materials.

The product was classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

· Safety phrases:

Keep in a cool place.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Please refer to the section 3 for NFPA and HMIS Hazard Codes.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

GENERAL DISCLAIMER

For terms and conditions, including limitation of liability, please refer to the purchase agreement in effect between Linde Inc. (or any of its affiliates and subsidiaries) and the purchaser.

· Department issuing MSDS: Customer Service Centre: 1-866-385-5349

· Abbreviations and Acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service (Division of the American Chemical Society)

DOT: US Department of Transportation

EINECS: European Inventory of Existing Commercial Chemical Substances

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

HMIS: Hazardous Material Identification System

IATA: International Air Transportation Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transportation Association"

ICAO: International Civil Aviation Association

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization (ICAO)

IMDG: International Marine Code for Dangerous Goods

WHIMS: Workplace Hazardous Material Information System

LC50: Lethal Concentration, 50 Percent

LD50: Lethal Dose, 50 Percent

EL: ExposureLlimit per ACGIH TLV

EV: Permissible Exposure Limit per OSHA

N/A: Not Applicable