Material Safety Data Sheet



Oxygen (Gas)

1. Product and company identification

Product name : Oxygen (Gas)
Synonym : Oxygen.

Trade name : Oxygen/ALIGAL™ 3/LASAL™ 2003

Material uses : Various/Special atmospheres for food./Laser applications.

CAS number : 7782-44-7

Supplier/Manufacturer : Air Liquide Canada Inc.

1250, René-Lévesque West, Suite 1700

Montreal, QC H3B 5E6 www.airliquide.ca 1-800-817-7697

Prepared by : IHS

In case of emergency : (514) 878-1667

2. Hazards identification

Physical state : Gas. [Compressed gas.]

Color : Colorless.
Odor : Odorless.

Emergency overview

Signal word : DANGER!

Hazard statements : OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. HIGH

PRESSURE GAS.

Precautions : Contains gas under pressure. In a fire or if heated, a pressure increase will occur and

the container may burst or explode. Keep away from combustible material. Do not puncture or incinerate container. Avoid breathing gas. Use only with adequate

ventilation. Keep container tightly closed and sealed until ready for use.

Routes of entry : Dermal contact. Eye contact. Inhalation.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : As this product is a gas, refer to the inhalation section.

Skin : May cause skin irritation. Contact with rapidly expanding gas may cause burns or

frostbite.

Eyes : May cause eye irritation. Contact with rapidly expanding gas may cause burns or

frostbite.

Potential chronic health effects

Chronic effects
 Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

2. Hazards identification

Fertility effects : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : No specific data.

Ingestion: No specific data.Skin: No specific data.Eyes: No specific data.

Medical conditions aggravated by over-

exposure

: None known.

3. Composition/information on ingredients

| Name | CAS number | % |
|--------|------------|-----|
| Oxygen | 7782-44-7 | 100 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

| Eye contact | : Check for and remove any contact lenses. | Immediately flush eyes with plenty of water |
|-------------|--|---|
| Lye contact | . Check for and remove any contact lenses. | ininediately lidest eyes with pierty of water |

for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical

attention immediately.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes

while removing contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention immediately.

Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if

respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

Ingestion: As this product is a gas, refer to the inhalation section.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Antidote information

| Product/ingredient name | Antidote information |
|-------------------------------|----------------------|
| No antidote information known | |

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : Contains gas under pressure. Contact with combustible material may cause fire. This material increases the risk of fire and may aid combustion. In a fire or if heated, a

pressure increase will occur and the container may burst or explode.

Extinguishing media

Suitable: Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

6/1/2014. Canada 2/9

5. Fire-fighting measures

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products

: No specific data.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8). If leak is in user's equipment, be certain to purge piping with an inert gas prior to attempting repairs. Never fix a leak while the system is under pressure. If leak is on container or container valve, contact the closest Air Liquide Canada location.

Environmental precautions

Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.

Large spill

: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Keep away from combustible material. Keep reduction valves free from grease and oil. Valve protection caps must remain in place unless cylinder is secured with valve outlet piped to usage point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow to the cylinder. Do not tamper with (valve) safety device. Close valve after each use and when empty.

Storage

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 52°C/125°F. Cylinders must be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in - first out" inventory system to prevent full cylinders being stored for excessive periods of time. See NFPA 430, Code for the Storage of Liquid and Solid Oxidizers. Store in accordance with local regulations. Store in a segregated and approved area. Store in a dry, cool and well-ventilated area,

6/1/2014. **Canada** 3/9

7. Handling and storage

away from incompatible materials (see Section 10). Protect from sunlight. Separate from reducing agents and combustible materials. Keep container tightly closed and sealed until ready for use.

8. Exposure controls/personal protection

Occupational exposure limits

No exposure limit value known.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

6/1/2014. **Canada** 4/9

Physical and chemical properties 9.

Physical state : Gas. [Compressed gas.]

Flash point : Not applicable. : Not available. **Auto-ignition temperature** : Not available. Flammable limits Color : Colorless. Odor : Odorless. Molecular weight : 32 g/mole

: 02 Molecular formula

pН : Not available.

Boiling/condensation point : -183.11°C (-297.6°F) Melting/freezing point : -218.55°C (-361.4°F) : -118.15°C (-180.7°F) **Critical temperature**

: Not available. **Density** : Not available. Vapor pressure : 1.1 [Air = 1] Vapor density **Odor threshold** : Not available. **Evaporation rate** : Not available. **Viscosity** : Not available. Solubility : Not available. Water solubility (g/l) : 0.04 g/l 0.65 LogK_{ow}

Stability and reactivity 10.

Chemical stability : The product is stable. **Conditions to avoid** : No specific data.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials, reducing

materials and combustible materials.

grease oil

Hazardous decomposition

products

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

: Hazardous reactions or instability may occur under certain conditions of storage or use. Conditions may include the following:

contact with combustible materials Reactions may include the following: risk of causing or intensifying fire

Under normal conditions of storage and use, hazardous polymerization will not occur.

Toxicological information 11.

Acute toxicity

Not available.

Chronic toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitizer

Not available.

Carcinogenicity

Classification

Not available.

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

Ecological information 12.

Ecotoxicity : This product shows a low bioaccumulation potential.

Aguatic ecotoxicity

Not available.

Persistence/degradability

Not available.

Partition coefficient: n-

octanol/water

0.65

Bioconcentration factor

: Not available. **Mobility** Not available. : Not available.

Toxicity of the products of

biodegradation

Other adverse effects : No known significant effects or critical hazards.

13. **Disposal considerations**

Waste disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Empty pressure vessels should be returned to the supplier. Waste packaging should be recycled.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

13. Disposal considerations

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|------------------------|-----------|-----------------------|-----------|-----|--------------------|---|
| TDG Classification | UN1072 | OXYGEN, COMPRESSED | 2.2 (5.1) | - | 2 2 0 551 | Explosive Limit and Limited Quantity Index 0.125 ERAP Index 3000 Passenger Carrying Ship Index 50 Passenger Carrying Road or Rail Index 75 |
| IMDG Class | UN1072 | OXYGEN, COMPRESSED | 2.2 (5.1) | - | O | Emergency schedules (EmS) _F-C_, _S-W_ Special provisions 355 |
| IATA-DGR Class | UN1072 | Oxygen, compressed | 2.2 (5.1) | - | O | Passenger and Cargo Aircraft Quantity limitation: 75 kg Packaging instructions: 200 Cargo Aircraft Only Quantity limitation: 150 kg Packaging instructions: 200 Limited Quantities - Passenger Aircraft Quantity limitation: Forbidden Packaging instructions: Forbidden Special provisions A175, A202 |

PG*: Packing group

15. Regulatory information

United States inventory (TSCA 8b)

: This material is listed or exempted.

WHMIS (Canada)

: Class A: Compressed gas. Class C: Oxidizing material.

Canadian lists

Canadian NPRI : This material is not listed.

CEPA Toxic substances : This material is not listed.

Regulatory information 15.

Canada inventory

: This material is listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists

: Australia inventory (AICS): This material is listed or exempted. China inventory (IECSC): This material is listed or exempted.

Japan inventory: Not determined.

Korea inventory: This material is listed or exempted. Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): This material is listed or exempted.

Philippines inventory (PICCS): This material is listed or exempted. Taiwan inventory (CSNN): This material is listed or exempted.

Chemical Weapons

I Chemicals

Convention List Schedule

Chemical Weapons Convention List Schedule

II Chemicals

Chemical Weapons

Convention List Schedule

III Chemicals

: Not listed

: Not listed

: Not listed

16. Other information

Label requirements

OXIDIZER. CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE. HIGH PRESSURE GAS.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

: 6/1/2014. **Date of issue** Date of previous issue : 6/15/2011.

Indicates information that has changed from previously issued version.

Notice to reader

16. Other information

THE INFORMATION, RECOMMENDATIONS AND DATA CONTAINED IN THIS DOCUMENT ARE INTENDED TO BE USED BY PROPERLY TRAINED AND QUALIFIED PERSONNEL ONLY AND AT THEIR SOLE RISKS AND DISCRETION. THE INFORMATION, RECOMMENDATIONS AND DATA HEREIN CONTAINED ARE DERIVED FROMSOURCES WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, AIR LIQUIDE CANADA INC. MAKES NO REPRESENTATION AND GIVES NO WARRANTY OF ANY KIND WHATSOEVER WITH RESPECT TO THEIR ACCURACY OR COMPLETENESS AND ASSUMES NO LIABILITY FOR DAMAGES OR LOSS ARISING DIRECTLY OR INDIRECTLY FROM THEIR USE, WHETHER PROPER OR IMPROPER.

Notes ALIGAL™: Trademark of L'Air Liquide S.A.

LASAL™: Trademark of L'Air Liquide S.A.